

THOMSON DELPHION		RESEARCH	PRODUCTS	INSIDE DELPHION
Home	About Us	My Account Products	Search: Quick/Number Boolean Advanced Derwent	

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Work File](#)

View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent](#)

[Email this to a](#)

Title: JP62154555A2: BATTERY

Derwent Title: Battery sealing material - comprising isobutylene! polymer contg. wax
NoAbstract Dwg 1/1 [\[Derwent Record\]](#)

Country: JP Japan

Kind: A (See also: [JP5058219B4](#))

Inventor: YANAGI TOSHIO;
GOSHI YOSHIHIRO;

Assignee: NIPPON PETROCHEM CO LTD
[News, Profiles, Stocks and More about this company](#)

Published / Filed: 1987-07-09 / 1985-12-27

Application Number: JP1985000292922

IPC Code: H01M 2/08;

Priority Number: 1985-12-27 JP1985000292922

Abstract: PURPOSE: To provide a battery having good electrolyte leakage resistance by using a sealant comprising isobutylene family polymer containing wax.

CONSTITUTION: A gap 5 in a battery sealing part is sealed with a sealant 4 made of a polymer mainly comprising isobutylene having a mean molecular weight of 700 ~ 10,000 containing 1 ~ 30wt.% wax. As the wax, animal and plant wax and preferably hydrocarbon wax such as paraffin wax, microcrystalline wax, polyethylene wax, and atactic polypropylene (APP) wax is used. Isobutylene polymer having mean molecular weight less than 700 has low viscosity and its sealing ability is insufficient. isobutylene polymer having mean molecular weight exceeding 10,000 has too high viscosity and it makes coating difficult.

COPYRIGHT: (C)1987,JPO&Japio

INPADOC

None

Get Now: [Family Legal Status Report](#)

Legal Status:

Family: [Show 2 known family members](#)


Best Available Copy

Forward References:

Go to Result Set: [Forward references \(1\)](#)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US6586912	2003-07-01	Tsukamoto; Hisashi	Quallion LLC	Method and apparatus for amplitude limiting battery temperature spikes

Other Abstract DERABS C87-231158 DERC87-231158



Info:



[Nominate this for the Gallery...](#)



© 1997-2004 Thomson

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)



(19)

(11) Publication number: **62154:**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **60292922**(51) Intl. Cl.: **H01M 2/08**(22) Application date: **27.12.85**

(30) Priority:	(71) Applicant: NIPPON PETROCHEM CO LT
(43) Date of application publication: 09.07.87	(72) Inventor: YANAGI TOSHIO GOSHI YOSHIHIRO
(84) Designated contracting states:	(74) Representative:

(54) BATTERY**(57) Abstract:**

PURPOSE: To provide a battery having good electrolyte leakage resistance by using a sealant comprising isobutylene family polymer containing wax.

CONSTITUTION: A gap 5 in a battery sealing part is sealed with a sealant 4 made of a polymer mainly comprising isobutylene having a mean molecular weight of 700 ~ 10,000 containing 1 ~ 30wt.% wax. As the wax, animal and plant wax and preferably hydrocarbon wax such as paraffin wax, microcrystalline wax, polyethylene wax, and atactic polypropylene (APP) wax is used. Isobutylene polymer having mean molecular weight less than 700 has low viscosity and its sealing ability is insufficient. isobutylene polymer having mean molecular weight exceeding 10,000 has too high viscosity and it makes coating difficult.

COPYRIGHT: (C)1987,JPO&Japio

